



Abrasive products

## A-FLEX SAND10

### Properties

- delivery NR/SBR hose for abrasive materials
- available, on request, antistatic version

### Applications

- delivery hose, sand and bead blasting application

### Construction

- inner tube: NR/SBR rubber, black, antistatic, abrasion resistant
- reinforcement: synthetic textile and, on request, copper earthing wire
- cover: black, smooth, antistatic cloth impression NR/SBR rubber, abrasion ageing and ozone resistant



**Code - B8G01....**

**Base Material - NR**

**Operating Temperature - -40 ÷ +70 °C**

**Pressure - 10 bar**

**Vacuum - n.d.**

**Diameter Range - 25 ÷ 102 mm**

**Key Feature - n.d.**

inner Ø	outer Ø	wall thickness	working pressure	bursting pressure	weight
mm	mm	mm	bar	bar	kg/m
25	38	6,50	10	30	0,770
32	46	7,00	10	30	1,030
38	54	8,00	10	30	1,350
51	70	9,50	10	30	2,160
64	83	9,75	10	30	2,770
76	101	12,50	10	30	4,210
100	125	12,50	10	30	7,140
102	136	17,00	10	30	7,430

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - nov\_17 rbd