



Abrasive products

A-FLEX ABR

Properties

- flexible hose for dust extraction, ventilation system, industrial ventilation
- suitable for dust collection and pneumatic conveying of materials such as metal shavings and abrasive powders foundry
- anti-static: $R < 10^6 \Omega$
- smooth end sleeves on request

Applications

- industry sites
- shipyards
- construction sites

Construction

- inner tube: NR rubber, black, smooth
- reinforcement: synthetic textile with embedded metallic helix
- cover: weather and ozone resistant NR/SBR rubber, black, corrugated, fabric impression



Code - A8G13....

Base Material - NR

Operating Temperature - $-30 \div +80$ °C

Pressure - 0,50 bar

Vacuum - 6,12 ÷ 9,18 mtH₂O

Diameter Range - 25 ÷ 152 mm

Key Feature - Anti-static, Spiral hose

inner Ø	vacuum	bending radius	weight
mm	mtH ₂ O	mm	g/m
25	9,18	75	580
30	9,18	90	660
32	9,18	96	690
35	9,18	105	750
40	8,16	120	820
45	8,16	135	1050
50	8,16	150	1160
60	8,16	180	1440
65	6,12	195	1590
70	6,12	210	1610

inner Ø	vacuum	bending radius	weight
mm	mtH ₂ O	mm	g/m
75	6,12	225	1700
80	6,12	240	1620
90	6,12	270	2210
100	6,12	300	2390
110	6,12	330	3450
115	6,12	345	3620
120	6,12	360	3520
127	6,12	381	3950
152	6,12	456	4950

ATAG reserves the right to make changes without notice, by virtue of any quality improvements and/or product specifications - ott_17 rbd